




CURVED SERIES AR400, AR401, AR402



SLAT PROFILES





FEATURES & BENEFITS

- Insulation
- Added security
- Wide range of colours
- Minimum roll up size
- Style choices
- Reduced greenhouse emissions
- Protection from the elements
- Light control
- Sound dampening

| TECHNICAL SPECIFICATIONS | |
|--------------------------------|---------------|
| Weight (per m²) | 4kg |
| Maximum Curtain Width | 3.6m |
| Maximum Area (m²) | 7.7 |
| Gauge of Aluminium | 0.32mm |
| Profile Slat Height | 40mm |
| Profile Slat Thickness | 9mm |
| Standard Guide Dimensions | 53mm |
| Standard Bottom Bar Dimensions | 50mm |
| Standard Axle | 50mm circular |

The Rollashield Residential Curved Series profiles have been designed specifically to suit the domestic roller shutter market in Australia but are also ideal with many commercial applications. The slat is roll formed in our Adelaide manufacturing facility to the highest of world standards using German built roll forming machines which are the most advanced of their type in the world.

The Rollashield Residential Curved Series slat is a double walled cavity with PU foam injected during the roll forming process. This process provides economical strength and insulation qualities while maintaining exceptional working performance of the slat. The curved shape of the slat provides optimal lateral strength and minimal roll sizes, offering a much smaller head box size.

The Rollashield curved series is available in three different styles, the 400 with profile lines on the convex side and a smooth finish on the concave, the 401 with a smooth finish on both sides and the 402 with profile lines on both sides.

BOX COLOUR OPTIONS












ROLLER SHUTTER COLOUR OPTIONS





SAND



Sand



CONTROL OPTIONS





Strap

MANUAL

Winder

Spring Assist

- - -



Grey



Black

MOTORISED







Beige





ODS with E-Port

1,0





SOMFY 240V

Brown

Green

Red

Woodland Grey

Deep Ocean Blue

Please note: Colours displayed are a guide only and have been matched as closely as possible. Due to the nature of the printing process, some degree of colour variation may occur. We recommend that you use production line prepared samples for final colour selection or approval.

SOMFY 240V with Key Switch SOMFY 240V RTS with Transmitter

SOMFY 240V with CSI override

BOXING OPTIONS

SQUARE BOXING (SQ45)

| Sizes Available | Maximum Overall Height |
|-----------------|------------------------|
| 150mm | 1300mm |
| 165mm | 1700mm |
| 180mm | 2135mm |
| 205mm | 3000mm |
| 230mm | 3800mm |
| 250mm | 4400mm |

Please note: Only when using Ozroll's 50mm circular axle.

ROUND BOXING (RD360)

| Sizes Available | Maximum Overall Height |
|-----------------|------------------------|
| 140mm | 1140mm |
| 160mm | 1650mm |
| 180mm | 2000mm |
| 200mm | 2800mm |
| | |

Please note: Only when using Ozroll's 50mm circular axle.

